E-Series Video Borescopes

The E-Series Video Borescope features diameters of 2.0 and 2.8mm. The new small diameters allow our customers to transition from fiber-based solutions to modern-day video technology. The E-Series Video Borescopes offer 4-way joystick articulation, image and video capture, and 4-hour battery life combined with a compact and durable design. The Hawkeye E-Series design allows end-users to easily remove and replace the insertion tube, eliminating repair downtime.



E-Series Video Borescopes Specifications					
Diameter	2.0mm and 2.8mm (.078 and .110") (+/- 0.2mm)				
Length	1, 2 and 3 meters				
Articulation	150° (+/- 10°)				
Field of View	100° Diagonal (+/- 10°)				
Depth of Field	3-50mm				
Direction of View	0°				
Sheath	Tungsten Braid				
Camera	400x400				
Display	3.5" HD Display				
Illumination	Integrated White LED (Tip LED 2.0mm)				
Interface	HDMI, USB, SD Card				
Battery	4hr, 3.7V, 3200 mAh				
Recording Media	JPEG/BMP, MPEG4				
Operating Temp	Probe: - 20 to +60C (-4 to +140 F) : Display Unit: -10to +50C (14 to +122F)				
Storage Temp	- 20 to + 60 C (-4 to +140 F)				
Weight	1.5lb				
Environmental	Sheath: IP67				

E-Series Video Borescopes						
Diameter	Length	Articulation	Sheath	Model		
2.0mm (.078")	1 meter (3' 3")	4-Way Joystick	Tungsten	VES 020 1000 4		
2.0mm (.078")	2 meter (6' 6")	4-Way Joystick	Tungsten	VES 020 2000 4		
2.0mm (.078")	3 meter (9' 9")	4-Way Joystick	Tungsten	VES 020 3000 4		
2.0mm (.078")	4.5 meter (14' 9")	Non-Articulating	Tungsten	VES 020 4500 NA		
2.8mm (.110")	1 meter (3' 3")	4-Way Joystick	Tungsten	VES 028 1000 4		
2.8mm (.110")	2 meter (6' 6")	4-Way Joystick	Tungsten	VES 028 2000 4		
*Kita lashidan Nidan Barananan CD Card CD//ICD Adaptar Charging Cables and Burgard Carrying Case						

*Kits Include: Video Borescope, SD Card, SD/USB Adapter, Charging Cables and Rugged Carrying Case.